

801 Series AWWA C515 Resilient Seated Gate Valve, Flanged Ends



SPECIFICATIONS

- WORKING PRESSURE: 300 PSI
- DESIGN CONFORMS: AWWA C509/C515
- FLANGED CONFORMS: AWWA C509/C515
- TEST & INSPECTION: AWWA C509/C515
- WORKING TEMPERATURE: -4°F TO 185°F
- FUSION BONDED EPOXY COATED

COMPONENTS

| NO. | PART NAME | MATERIAL |
|-----|------------------|--------------------------------|
| 1 | TOP BOLTS | STAINLESS STEEL AISI 304 |
| 2 | OPERATING NUTS | DUCTILE IRON ASTM A536 |
| 3 | DUST CAP | RUBBER EPDM |
| 4 | GLAND | DUCTILE IRON ASTM A536 |
| 5 | O-RING | RUBBER EPDM |
| 6 | STEM BUSHING | NYLON / BRASS ASTM B124 C37700 |
| 7 | STEM | STAINLESS STEEL AISI 304 |
| 8 | O-RING | RUBBER EPDM |
| 9 | BONNET | DUCTILE IRON ASTM A536 |
| 10 | WEDGE NUT GASKET | RUBBER EPDM |
| 11 | WEDGE NUT | BRASS |
| 12 | WEDGE | DUCTILE IRON EPDM |
| 13 | BONNET GASKET | RUBBER EPDM |
| 14 | BODY | DUCTILE IRON ASTM A536 |
| 15 | GLAND BOLT | STAINLESS STEEL |
| 16 | BONNET BOLT | STAINLESS STEEL |

