



Dimensions in inch						
Size	3"	4"	6"	8"	10"	12"
L	9-1/2	10	11-1/2	12-1/2	14-3/4	14-7/8
H	11-5/8	13-3/4	17-15/16	21-7/16	25-3/8	28-3/4
D	7-11/16	9-1/8	11-1/8	13-5/16	15-5/8	17-7/8

17	Screw	Carbon Steel	A307 Grade B
16	Washer	Stainless Steel	A276 Type 304
15	Bolt	Carbon Steel	A307 Grade B
14	Operating Nut	Ductile Iron	A536 65-45-12
13	Dust Ring	Rubber	D2000 NBR
12	O-Ring	Rubber	D2000 NBR
11	Gland	Ductile Iron	A536 65-45-12
10	O-Ring	Rubber	D2000 NBR
9	Thrust Collar	Bronze	B148 C95200
8	O-Ring	Rubber	D2000 NBR
7	Bonnet	Ductile Iron	A536 65-45-12
6	Bolt	Carbon Steel	A307 Grade B
5	Gasket	Rubber	D2000 EPDM
4	Stem	Stainless Steel	A276 Type 304
3	Wedge Nut	Bronze	B148 C95200
2	Wedge	Ductile Iron EPDM Encapsulated	A536 65-45-12
1	Body	Ductile Iron	A536 65-45-12
No	Part Name	Material	A.S.T.M.


Southern Valve & Fitting USA, Inc.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	REV	DESCRIPTION	DATE	BY	TITLE: NRS UL/FM Resilient Seated Gate Valve MJxMJ Ends
MATERIAL	A	INITIAL ISSUE	04/30/2019	THX	
WEIGHT					807 Series
FINISH					
DO NOT SCALE DRAWING					SCALE: NONE-UNLESS NOTED
					SHEET 1 OF 1