

## 807IP Series Mechanical Joint Post Indicator Valve

### SPECIFICATIONS

- AWWA C515 COMPLIANT
- NON-RISING STEM
- COMES WITH INDICATOR POST FLANGE AND A 2" OPERATING NUT
- TRIPLE O-RING STEM SEAL
- NPT PLUG ON BODY
- MECHANICAL JOINT CONFORMS TO ANSI/AWWA C153/A21.53
- UL/FM APPROVED

### WORKING PRESSURE


- 300 PSI

### WORKING TEMPERATURE

- 33°F TO 170°F

### CORROSION PROTECTION

- INTERNALLY AND EXTERNALLY FUSION BONDED EPOXY POWDER COATED (FBE)



### COMPONENTS

PART NAME	MATERIAL
BODY	DUCTILE IRON A536 65-45-12
WEDGE	DUCTILE IRON WITH EPDM COATING
WEDGE NUT	BRONZE ASTM B62
STEM	STAINLESS STEEL AISI 316
THRUST COLLAR	BRONZE ASTM B62
BONNET	DUCTILE IRON A536 65-45-12
GASKET	EPDM
GLAND	DUCTILE IRON A536 65-45-12
O-RING	EPDM
POST FLANGE	DUCTILE IRON A536 65-45-12
OPERATING NUT	DUCTILE IRON A536 65-45-12
NPT PLUG	MALLEABLE IRON
INDICATOR FLANGE BOLTS	STAINLESS STEEL AISI 304
BONNET BOLTS	STAINLESS STEEL AISI 304

### DIMENSIONS

SIZE	L	H	D	WEIGHT (KG)
3"	9 1/2	11 5/8	-	20.4
4"	10	13 3/4	12	32
6"	11 1/2	17 15/16	12	52.5
8"	12 1/2	21 7/16	12	80
10"	14 3/4	25 3/8	12	118
12"	14 7/8	28 3/4	12	175

